

Vitesse et couple préconisés par :
Speed and torque that are recommended by :

K3



Endy 6200
micromotor and apex locator



Endo Master 2
Endy 6200 previous version

K3 G-PACK KERR FILES	RPM	TORQUE N/CM
SEQUENCE 1 SOFT NARROW CANALS		
25/12 S	350	2.5
25/10 S	300	2.5
25/08 S	300	2.5
25/06	300	2
25/04	300	1.5
25/02	300	1.25
25/04	300	1.5
25/06	300	2
SEQUENCE 3 HARD PACK PROCEDURE		
25/10 S	300	2.5
25/08 S	300	2.5
40/06	300	2.5
35/06	300	2
30/06	300	2
25/06	300	2

→ 25/12, 25/10 & 25/08 OPENER

→ 25/10 & 25/08 SHAPER

*Ces valeurs sont données à titre indicatives et ne peuvent en aucun cas engager la responsabilité de IONYX.
 These values are for information purposes only and cannot engage IONYX responsibility under no circumstance.*

**Your partner
 for over 25 years !**



ionyx | designer - manufacturer | apex locators - micromotors

34 rue de Fleurenne - F-33290 BLANQUEFORT | T. +33 5 56 35 34 27 - F. +33 5 56 95 16 20 | ionyx@ionyx.eu - www.ionyx.eu